

















## Specifications


	<b>Voltage (V)</b>	180-250V ac
<b>Hz</b>	<b>Frecuency (Hz)</b>	50-60
	<b>Dimming</b>	
	<b>IP Tightness index</b>	20
	<b>Body color</b>	White
	<b>Diffuser Material</b>	PC-O
	<b>Body</b>	AL
<b>K</b>	<b>Colour temperature</b>	3.000K
	<b>CRI Colour rendering index</b>	>80
	<b>Opening angle</b>	120°
	<b>Measures</b>	175x30
	<b>Operating temperature</b>	-5°C~+35 °C
	<b>Flux (lm)</b>	1.516lm
	<b>Electrical isolation</b>	II
	<b>Lifetime</b>	(L70B50>) 50.000h
	<b>L70 B10&gt;(500&lt;I≤1.000mA)</b>	L70 >50.000h

## References



	W	K				
<b>381482</b>	14W	3.000K	Blanco	150-155	175x30	Si

## Dimensions



## Photometry



### Info




Vous avez besoin d'un driver DALI

---

## On request

---



Emergency kit 2hBajo el campo de configuración se añade solo este texto, en los 4 idiomas definidos



---

## Technologies

---



---

### CELLTECH



CELLTECH technology is a revolutionary feeding system for luminaires that allow the extraction and exchange of drivers that facilitates and simplifies the installation and mounting of luminaires. CELLTECH drivers are available without regulation and with 1-10V regulation and C-TOUCH.

---