























Specifications


	Voltage (V)	180-250
Hz	Frecuency (Hz)	50-60
Φ	Power factor (Cos fi)	$\geq 0,9$
	Dimming	
	IP Tightness index	20
	IP installed Sealing rating	40
	Body color	9006
	Diffuser Material	PC-O
	Body	PC
K	Colour temperature	4000k
	CRI Colour rendering index	≥ 80
	Opening angle	120°
	Measures	125x125x30
	Mounting position	Recessed Ceiling
	Operating temperature	-5 +35
Φ_{LUM}	Flux (lm)	563lm
	Electrical isolation	II
	Lifetime	50.000h
	L70 B10>(500<I≤1.000mA)	L70 >50.000h

References



	W	K				
387446	6W	4000k	9006	100x100	125x125x30	Si

Dimensions



Photometry





On request



Emergency kit 2hBajo el campo de configuración se añade solo este texto, en los 4 idiomas definidos



DALI-CTOUCH-Only 20W / 14W

Accessories



532211

DRIVER KENTAU 6W
1-10V



Technologies



CELLTECH



CELLTECH technology is a revolutionary feeding system for luminaires that allow the extraction and exchange of drivers that facilitates and simplifies the installation and mounting of luminaires. CELLTECH drivers are available without regulation and with 1-10V regulation and C-TOUCH.



Solutions

S



Pack CTE



description



Regulación por aporte de luz natural para cumplir con las exigencias del CTE. Control independiente de dos líneas de luminarias regulables DALI con sensor para instalar en luminaria o caja en superficie. Preconfigurado para poner en funcionamiento de manera sencilla.



Pack AULAS



description



Regulación por aporte de luz natural y presencia stand alone. Sistema de control de iluminación para cumplir con las exigencias del CTE y optimizar el uso de la energía aprovechando el aporte de luz natural y apagado automático en caso de ausencia.



Pack BLUETOOTH



description



Dispositivo que habilita el control de luminaria DALI a través de cualquier terminal Bluetooth® vía APP gratuita que nos ofrece el control de regulación de flujo, color, configuración de escenas, comportamiento vinculado a horarios.



Driver DALI

description



Info



For more information on the different solutions compatible with this luminaire, consult the following BIDI codes or on the web www.grupoprilux.com