

















Specifications


	Voltage (V)	180-250V ac
Hz	Frecuency (Hz)	50-60
	Dimming	No/Non/Não
	IP Tightness index	20
	Body color	9006
	Diffuser Material	PC-O
	Body	AL
K	Colour temperature	4.000K
	CRI Colour rendering index	>80
	Opening angle	120°
	Measures	175x175x30
	Operating temperature	-5°C~+35 °C
	Flux (lm)	1.548lm
	Electrical isolation	II
	Lifetime	(L70B50>) 50.000h
	L70 B10>(500<I≤1.000mA)	L70 >50.000h

References



	W	K				
387521	14W	4.000K	9006	150 x 150	175x175x30	No

Dimensions



Photometry



Info



Vous avez besoin d'un driver DALI

On request



Emergency kit 2hBajo el campo de configuración se añade solo este texto, en los 4 idiomas definidos

Accessories



532198

DRIVER KENTAU 14W
1-10V



543125

DRIVER KENTAU 14W
CTOUCH



507332

DRIVER KENTAU 14W
DALI



Technologies



CELLTECH



CELLTECH technology is a revolutionary feeding system for luminaires that allow the extraction and exchange of drivers that facilitates and simplifies the installation and mounting of luminaires. CELLTECH drivers are available without regulation and with 1-10V regulation and C-TOUCH.
